

CPC Ozone Friendly Refrigeration Oil 68

- CPC Ozone Friendly Refrigeration Oil 68 is specially formulated with selected polyol ester as base oil, and is mainly used in refrigerating compressors with HFC-134a refrigerant where environmental protection is a major concern.
- The oil possesses excellent lubricity, anti-wear property, low pour point, chemical and thermal stability to ensure the operation safety of the system, and to extend the operation life of refrigerating compressor.
- Packages: (1) 200 liter drum
 - (2) 19 liter pail
- The typical data are listed as follow:

Grade No.	68
Sp. Gr., 15.6°C/15.6°C,D4052	0.9711
Viscosity, Kin., cSt @40°C,D445	63.0
@100°C,D445	8.30
Viscosity Index, D2270	100
Pour Point, °C, D6749	-42
Color, D1500	L0.5
Flash Point, COC, °C, D92	254
Acid Number, mg KOH/g, D664	0.01
Copper Corrosion, 100°C, 3hrs,D130	1a
Appearance	Clear
Miscibility, °C (10% Oil in HFC-134a)	-42
Product No.	LA62505

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.