



## CPC Super Low Smoke Two-Stroke Engine Oil

- CPC Super Low Smoke Two-Stroke Engine Oil is tied in environmental-friendly trend to be developed a super low smoke synthetic two-stroke engine oil by applying the latest formulation technology. The smoke index is over 170 and the quality of the oil exceeds the standards of JASO M345 FC.
- The oil provides ultra-high engine lubrication and prevents the contamination of the spark plug engine, and meet the international standard of ISO GD grade. With tough film, the oil provides the effects of high clean, anti-wear, reducing engine contamination, and engine life prolongation.
- The oil can be applied to various models of two-stroke engine motorcycle and be applied to motorcycles equipped with catalytic converters.
- Package: 0.7 liter bottle, 0.7 liter\*12 case
- The typical data are listed as follow:

SAE Viscosity No.	20
Sp. Gr., 15.6°C/15.6°C, D4052	0.8645
Viscosity, Kin., cSt @40°C, D445	52.73
@100°C, D445	8.20
Viscosity Index, D2270	127
Pour Point, °C, D6749	-27
Flash Point, COC, °C, D92	94
Acid Number, mg KOH/g, D664	0.26
Base Number, mg KOH/g, D2896	1.47
Sulfated Ash, %, D874	0.14
Color, Visual	Dark Green
Product No.	LB52021

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.